



**WACKER
NEUSON**
all it takes!

Single direction vibratory plate VP1135A

5100029066

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Single direction Vibratory Plates](#) >> [Single direction vibratory plate VP1135A](#)



Single direction vibratory plate VP1135A

Material number 5100029066

Single direction vibratory plate for soil compaction

Product details

Compact single direction vibratory plate, for occasional compaction work

- Sturdy design for minimal maintenance effort: The V-belt drive with all-round protection provides for a particularly long operating duration of the V-belt. The base plate is made from wear resistant nodular cast iron.
- A large sturdy lifting eye allows for secure transport. The guide handle that can be folded forward converts the unit into a compact unit in no time
- Accessories, paving stone sliding mechanism as well as water tank with sprinkler set available here in the shop

Comes with

- Single direction vibratory plate for soil compaction
- Operation manual

Technical specifications

Single direction vibratory plate VP1135A

MECHANICAL - OUTPUT DETAILS

Centrifugal force	11,000 kN
Transmission	FKK-KR
Vibrations	5.880 1/min
Area capacity	533 m2/h
Forward Running	25,00 m/min
Gradeability	36,4 %
Vibrations (Hz)	98 Hz

MECHANICAL DETAILS

Length Drawbar in op. pos.	958 mm
Width	330 mm
Height	918 mm
Operating weight	61,0 kg
Ground clearance	467 mm

ENGINE

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder capacity	118 cm3
Fuel	Gasoline
Fuel management	Carburettor
Fuel consumption	1,00 L/Std

Inclined position max.	20,0 °
Cylinder	1
Tank capacity	2,50 l
Oil specification	SAE 10W-30
Oil filling max.	0,60 l
Power rating max.	2,6 kW
Standard (Effective power)	ISO 3046 IFN
Nominal Engine speed	3.600 1/min
Standard (Power max.)	SAE J1349
Operating power	2,1 kW
Engine speed (Power max.)	3.600 1/min
Effective power	2,6 kW
Oil filling min.	0,60 l
Standard (Operating power)	ISO 3046 IFN
Operating Engine speed	3.600 1/min
Exhaust-gas limit	EPA4/08
Spark plug(s)	NGK BP-6 ES
Starter type	Recoil starter
Oil volume incl. filter change	0,60 l
Air cleaner	dry air filter
Engine Manufacturer	Honda

ENVIRONMENT DATA

Storage temperature range	-15 - 40 °C
Sound level LpA	93,0 dB(A)
Sound power LWA, measured	104,0 dB(A)
Sound level LpA (Standard)	EN 500-4
Sound power LWA, guaranteed	105,0 dB(A)
Operating temperature range	-15 - 45 °C
Sound power LWA (Standard)	EN 500-4
HAV summation (Standard)	EN 500-4

HAV summation (average value)	4,7 m/s ²
-------------------------------	----------------------

Uncertainty in measurement HAV	0,5 m/s ²
--------------------------------	----------------------

ELECTRICAL SYSTEM

Electrode distance	0,7 - 0,8 mm
--------------------	--------------

Custom Attributes

Model serie	VP
-------------	----

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE